

Pillar Gauge Pod for 2011-2018 Jeep Wrangler JK

Please note that this pillar pod is a complete replacement and will require removal of the factory A-pillar trim.

⚠ WARNING Prior to installing the pillar pod, please make sure your vehicle does not have side curtain airbags.

1. Be sure to store the factory A-pillar trim in a safe location after being removed.
 - Using a T20 Torx Driver, remove the (2) screws holding up the sun visor and set the sun visor off to the side.
 - Using a Phillips head screwdriver, remove the push-in retainer in the lower A-pillar hole.
 - Remove the A-pillar corner trim by releasing the push-in retainer.
 - Unplug the electrical connector if equipped and set the corner trim off to the side.
 - Pull on the factory A-pillar trim to release the spring clip and remove from the vehicle.
2. Mock your pillar pod up to your Jeep's factory A-pillar corner trim, aligning the cutout on the pillar pod with the molded hole on the back side of the stock corner trim.
3. Once aligned, mark and drill (2) 7/32nd holes through both pieces.
 - ↳ **OPTIONAL STEP** Our pillar pods can be painted using ABS plastic paint. Be sure to scuff the surface of the pod using a scuff pad. This will allow the paint to properly adhere to the surface of the pod. Before applying paint to the pillar pod, ensure it is cleaned off and that there is no residue on the pod from scuffing it. Apply 2-3 even coats, waiting 10 minutes between coats to dry.
 - Be sure to follow the paint manufacturer's instructions while painting, in addition to proper safety procedures.
 - Please note that you will not be eligible to return this pod for a refund if painted.
4. Push the (2) included Flush-Mounted Retainers into the drill holes to secure the pillar pod and A-pillar together.
5. Connect the 2 1/16" [52mm] gauge wires to their sensors and power by following the instructions that are included with the gauges.
6. In the event you have to remove the pillar pod from the factory trim, carefully remove the fasteners using a panel pop tool.
7. Plug in the factory electrical connector, if it was equipped, and install your Jeep's factory A-pillar corner trim and pillar pod assembly back into your vehicle with the factory push-in retainer.
8. Reinstall the sun visor using a T20 Torx Driver.
9. Finally, reinstall the factory push-in retainer in the lower A-pillar hole.

All GlowShift Products are subject to the GlowShift Limited Warranty. Please visit <https://www.glowshiftdirect.com/warranty-policies> to review complete Warranty, Terms, and Conditions.